

## PAC GS3 Range

## Readers—HF

### 909020120 – PAC OneProx™ GS3 HF Mullion Reader

Designed to work in the most demanding of operating environments, HF Readers support installations which require reliability and security. The Mullion Reader is a compact reader that is ideal for fitting on the frame of a door, internally or externally.



Can be installed onto most door frames

- Supports the following ID Devices:
  - PAC Ops™ Lite
  - PAC Ops™
  - Wiegand (many variants)
- Integral Tamper circuit and Mounting Plate
- Reader line tamper configurable when used in conjunction with PAC 512 controllers

<b>Part Number(s)</b>	909020120 – PAC OneProx™ GS3 HF Mullion Reader
<b>Supported ID Device Formats</b>	PAC Ops™ Lite, PAC Ops™
<b>Supported Output Protocols</b>	PAC32, PAC64, Wiegand
<b>Audio / Visual Indicators</b>	Audible Sounder and Red/Green LEDs
<b>RFid Frequency</b>	High Frequency (13.56MHz)
<b>Maximum Read Range</b>	45 mm / 1.77 in.
<b>Tamper Output</b>	Certified to EN 50131-1 and EN 50131-3
<b>Recommended Cabling</b>	PAC output 6-core 24 AWG alarm cable (unscreened)
<b>Power input(s)</b>	12–24V DC, <90mA @ 12V DC
<b>Dimensions</b>	48 (w) x 105 (h) x 28 (d) mm / 1.89 (w) x 4.13 (h) x 1.10 (d) in.
<b>Weight</b>	0.150 kg / 0.331 lb
<b>Material</b>	UL rated Polycarbonate
<b>Operating Temperature</b>	-40°C to +66°C / -40°F to 151°F
<b>Operating Humidity</b>	10% to 85% Relative Humidity
<b>Warranty</b>	Lifetime against electronic failure
<b>Standards Compliance</b>	UKCA, CE, FCC, IC, RoHS & WEEE compliant
<b>Environment</b>	IP65 – Indoor / Outdoor weather resistant
<b>Intruder Grading</b>	Security Grade 3