

PAC GS3 Range

Readers—HF

909020121 – PAC OneProx™ GS3 HF Standard Reader

Designed to work in the most demanding of operating environments, HF Readers support installations which require reliability and security. The Mullion Reader is a compact reader that is ideal for fitting on the frame of a door, internally or externally. The Standard Reader is ideal for fitting into most standard electrical back boxes, internally or externally.



Can be installed onto most door frames

- Supports the following ID Devices:
 - PAC Ops™ Lite
 - PAC Ops™
 - Wiegand (many variants)
- Integral Tamper circuit and Mounting Plate
- Reader line tamper configurable when used in conjunction with PAC 512 controllers

Part Number(s)	909020121 – PAC OneProx™ GS3 HF Standard Reader
Supported ID Device Formats	PAC Ops™ Lite, PAC Ops™
Supported Output Protocols	PAC32, PAC64, Wiegand
Audio / Visual Indicators	Audible Sounder and Red/Green LEDs
RFid Frequency	High Frequency (13.56MHz)
Maximum Read Range	65 mm / 2.56 in.
Tamper Output	Certified to EN 50131-1 and EN 50131-3
Recommended Cabling	PAC output 6-core 24 AWG alarm cable (unscreened)
Power input(s)	12–24V DC, <90mA @ 12V DC
Dimensions	89 (w) x 115 (h) x 28 (d) mm / 3.50 (w) x 4.53 (h) x 1.10 (d) in.
Weight	0.290 kg / 0.639 lb
Material	UL rated Polycarbonate
Operating Temperature	-40°C to +66°C / -40°F to 151°F
Operating Humidity	10% to 85% Relative Humidity
Warranty	Lifetime against electronic failure
Standards Compliance	UKCA, CE, FCC, IC, RoHS & WEEE compliant
Environment	IP65 – Indoor / Outdoor weather resistant
Intruder Grading	Security Grade 3