

## Transmitters & Readers

## Remote Access Control

**SK9062B/A 868 MHz Transmitter RFID Proximity Reader, Blue 4 button**

**SK9062Y/A 868 MHz Transmitter RFID Proximity Reader, Yellow 4 button**

**SK9011/A RF Access Control Unit for 868 MHz transmitters + Remote Antenna**

**SK9014 Remote Antenna for 868 MHz Receiver (Optional)**

The Comelit Transmitter can provide long range access requests for entry via garage doors, gates, barriers, etc. The range can be extended up to 50m when used with the Comelit SK9011/A Receiver Unit and Comelit SK9014 Remote Antenna.

This is ideal for remote entry requests that typically include:

- gates
- barriers/shutters
- garage doors

The Transmitter can also be used as a MIFARE® RFID proximity credential.



SK9062B/A



SK9062Y/A

### Transmitters

<b>Part Number(s)</b>	<b>SK9062B/A</b> 868 MHz Transmitter, RFID Proximity Reader, Blue 4 button	<b>SK9062Y/A</b> 868 MHz Transmitter, RFID Proximity Reader, Yellow 4 button
<b>Visual Indicators</b>	3 colour LED Flashing RED/GREEN indicates new battery required	
<b>RFid Frequency</b>	High Frequency (13.56MHz)	
<b>RFid Technology</b>	Bi-technology support: 868MHz RF / MIFARE®	
<b>Read Range</b>	Up to 80-120 m / 262–394 ft. max. open field	
<b>Power Inputs</b>	3V CR2032 type batteries	
<b>Dimensions</b>	32 (w) × 76 (h) × 11 (d) mm / 1.26 (w) × 2.99 (h) × 0.43 in.	
<b>Weight</b>	0.02 kg / 0.04 lb	
<b>Material</b>	ABS housing available in two colours with raised 'dots' to identify button selection	
<b>Operating Temperature</b>	–20°C to +50°C / –4°F to 122°F	
<b>Warranty</b>	2 years	
<b>Compliance &amp; Directives</b>	UKCA, CE, RoHS, WEEE	

## Transmitters & Readers

## Remote Access Control



SK9011/A

### Receiver

<b>Part Number(s)</b>	<b>SK9011</b> RF Access Control Unit
<b>Visual Indicators</b>	Audible Sounder and Red/Green LEDs
<b>RFid Frequency</b>	High Frequency (13.56MHz)
<b>RFid Technology</b>	Bi-technology support: 868MHz RF / MIFARE
<b>Read Range</b>	Up to 50 m / 164 ft. max. free field
<b>Operating Voltage</b>	12V @ 24V AC or 12V @ 33V DC
<b>Power Consumption</b>	50mA when idle, 100mA when relay active
<b>Dimensions</b>	85 (w) × 55 (h) × 20 (d) mm / 3.35 (w) × 2.17 (h) × 0.79 in.
<b>Weight</b>	0.06 kg / 0.0 lb
<b>Material</b>	ABS housing
<b>Operating Temperature</b>	-10°C to +55°C / 14°F to 131°F
<b>Warranty</b>	2 years
<b>Compliance &amp; Directives</b>	UKCA, CE, RoHS, WEEE



SK9014

### Antenna

<b>Part Number(s)</b>	<b>SK9014</b> Remote Antenna for 868 MHz receiver
<b>Read Range</b>	Extends receiver range up to 50 m / 164 ft. max. free field
<b>Installation kit</b>	Supplied with surface mount bracket and 3m cable
<b>Warranty</b>	2 years
<b>Compliance &amp; Directives</b>	UKCA, CE, WEEE