KVV8501

MONO VISTO AND 7TOP KIT, VIP

The kit includes: 1 x art. VS8101A Visto Ethernet external unit for ViP system, 1 x art. TP6842 7TOP 7" hands-free Wi-Fi door entry monitor for ViP system, 1 x art. 1488 power injector for kit, 1 x art. 1441B 30W power supply unit. The kit is pre-programmed and ready to use, it is expandable with other products in the ViP catalog. Combined with the Comelit app, downloadable free of charge from the Google and Apple stores, it allows you to answer calls directly from your smartphone/tablet, both locally and remotely.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

PRODUCTS IN THE KIT

1488 **POWER INJECTOR FOR VIP KIT**

This device is designed to power the ViP KIT and allow it to manage the network. It is equipped with a two-pole terminal for connection of the power supply (48-56 VDC), guaranteeing a stable energy supply for the system. It also has two RJ45 Ethernet ports, one for connecting the ViP KIT to the external unit (EXT port) and one for connecting it to the internal unit (INT port). Its compact size (36 x 90 x 58 mm) and 2 DIN module format allow easy and safe DIN rail installation.

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

VS8101A VISTO ETHERNET EXTERNAL UNIT. VIP SYSTEM

Italian design Visto series wall-mounted doorbell unit for ViP IP video entry system. Complete with one call button, wide-angle colour camera, audio speaker and microphone. ViP and standard POE power supply. Dark graphite RAL9011 colour. Dimensions (W x H x D): 47x136x32 mm.

GENERAL DATA	
Type	Monoblock
Height (mm)	136
Width (mm)	47
Depth (mm)	28
Product weight (g)	155
Product color	Dark Graphite RAL9011
Type of finishing materials	ABS
Wall-mounted	Yes

COMPATIBLE SYSTEMS	
ViP	Yes

AUDIO FEATURES	
Technologies implemented	Full-Duplex, Echo canceling, Noise reduction

CAMERA FEATURES	
Camera	Colours
Sensor type	1/4" CMOS
Lens optical dimensions (mm)	1.6
Angle of view (H x V - °)	144 x 78
Video resolution	1280x720 (HD 720p)
Video compression	H.264

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

ELECTRICAL CHARACTERISTICS

Type of power supply	PoE
Supply voltage	37÷57 VDC (ViP)
PoE power supply	Standard IEEE 802.3af, 36÷57VDC, standard PoE
PoE class	Class 2
Absorption in stand-by (W)	1.39
Maximum absorption (W)	4.92

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1
Backlight colour	White
Removable terminals	Yes
Number of outputs (n°)	1
Type of outputs	Relay (C-NO, 1A@30VDC)

NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network	Ethernet 10/100 Mbit/s
IP address assignment	Auto IP, DHCP, Static

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

MAIN FUNCTIONS	
Number of auxiliary relays (n°)	1
Visual indications of system status	Yes
Acoustic signals of system status	Yes

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

TP6842 **7TOP 7” WI-FI HANDS-FREE VIP DOOR ENT. MONITOR**

7TOP door entry monitor for VIP systems with a 7-inch colour touchscreen, equipped with a mechanical lock-release key with backlit icon. A modern, attractive design that combines sturdiness with usability. It can be surface mounted using a metal backplate (included) to ensure it is firmly and securely anchored, or desktop mounted using a special stand (available to purchase separately). It can be powered via standard POE, 1440A distributor or a dedicated 48V power supply input. There is a MicroSD card slot on the side (not included) for uploading custom ringtones. Equipped with programmable local inputs, one programmable output and one additional ringtone output. Ethernet and Wi-Fi connectivity allows you to connect to the Comelit Cloud and receive calls via app on your smartphone, even when you’re not at home. Linux operating system, full-duplex hands-free audio and native support for H.264 and H.265 video formats. New icon-based graphical interface, for use in user or installer mode, customisable and easy to use. Many built-in functions, including Automatic updating, Video memo, Alarm management, Auto lock-release (Doctor), Silent mode (Privacy), Automatic answer (Hands-Free), Call divert. Dimensions (L x H x D): 210x120x21 mm. Colour: White/Black.

GENERAL DATA	
Height (mm)	120
Width (mm)	210
Depth (mm)	21
Product weight (g)	570
Product color	White RAL9003, Black RAL9005
Type of finishing materials	ABS, Glass
Flush-mounted	No
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
ViP	Yes

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

DISPLAY	
Display size (")	7
Type of display	TFT
Aspect Ratio	16:9
Touch screen	Yes, capacitive
Resolution (pixels)	1024x600

AUDIO FEATURES	
Type	Hands-free
Induction loop function	No
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 8 Ohm, 1W
Technologies implemented	Full-Duplex

ELECTRICAL CHARACTERISTICS	
Type of power supply	PoE
Supply voltage	37÷57 VDC (ViP)
PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)
Absorption in stand-by (W)	2.4
Maximum absorption (W)	6

HARDWARE FEATURES	
Type of buttons	Mechanical
Service buttons	Lock-release
Clamps	AL, GND, CFP, PAN, IN1, OUT1, S+, S-/GND // V+, V-
Removable terminals	Yes
Number of inputs (n°)	4
Number of outputs (n°)	1
Memory card supported	Micro-SD (not supplied)
Communication ports	Ethernet

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

HARDWARE FEATURES	
Type of connections/ports	RJ45
Ethernet ports (n°)	1
Network connection	RJ45
LED signaling (no.) (n°)	1

SETTINGS	
Loudspeaker volume	Yes
Microphone volume	Yes
Ringtone volume	Yes
Screen brightness control	Yes
Screen contrast	Yes

NETWORK AND COMMUNICATION PROTOCOLS	
Type of LAN network	Ethernet 10/100 Mbit/s
Type of Wi-Fi connection	2.4 GHz
IP address assignment	DHCP, AUTO IP, static IP
IoT connection to Comelit Cloud	Yes
Firmware update via Comelit Cloud	Yes
Operating system	Linux embedded
Comaptibility with Video Entry Comelit App	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
IP protection rating	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I (B1)
Certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

GENERAL FEATURES	
Door opener	Yes
Automatic door opening on call (Doctor)	Yes
Silent mode (Privacy)	Yes
Self Activation	Yes
Call to group addresses	Yes
CPS call	Yes
Intercom calls	Yes
Panic call	Yes
Call forwarding	Yes
Outside door call input	Yes
Customisable ringtone	Yes
Automatic answer (handsfree)	Yes
Video memory	Yes
Message for absent	Yes
Sending alarm calls	Yes
Actuator control	Yes
ViP anti-theft function	Yes
Multiple address	Yes
Integration with voice assistants	Yes
Receiving text messages	Yes
Receiving ViP messages	Yes
Led to additional signaling (no.) (n°)	1
Door open signaling	Yes
Acoustic signalling	Yes
Visual signalling	Yes
Date/time display	Yes

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

1441B **30W VIP SYSTEM POWER SUPPLY UNIT**

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm

MAIN FEATURES	
Supply voltage	110÷240 VAC
Output supply voltage	48VDC
Input connector	Terminal block
Applicable to DIN rail	Yes
Number of DIN modules (n°)	4

HARDWARE SPECIFICATIONS	
Product weight (g)	352

GENERAL DATA	
Height (mm)	62
Width (mm)	90
Depth (mm)	70
Type of finishing materials	ABS
Product color	White RAL9010
Operating temperature (°C)	-10 ÷ 50

COMPATIBILITY	
Vip system	Yes

AUDIO/VIDEO FEATURES	
Audio/video system	Yes

ELECTRICAL SPECIFICATIONS	
Power supply	100 - 240 VAC

The technical specifications are subject to change without prior notice.

KVV8501

MONO VISTO AND 7TOP KIT, VIP

ELECTRICAL SPECIFICATIONS	
Switching power supply	Yes
Maximum current absorption (mA)	900
Maximum power delivered (W)	30

GENERAL FEATURES	
DIN modules (no.) (n°)	6
DIN rail mounted	Yes
Visual signalling	Yes

The technical specifications are subject to change without prior notice.The technical specifications are subject to change without prior notice.