

**2738W/A****SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET**

Mini series door-entry phone with handset for Simplebus 2 audio systems. Equipped with a key button, button for additional services such as calls to the porter switchboard..., call volume adjustment, Silent mode (Privacy) and floor call input. Correct positioning of the handset on the base is facilitated by invisible magnetised panels. The additional board art. 2735 is available to purchase separately, for an additional button with voltage free contacts and call repetition. Fitted with terminal art. 1214/2C.

**AWARDS**DESIGN  
MILANO



**2738W/A**

**SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET**

**GENERAL DATA**

Height (mm)	190
Depth (mm)	28
Type of finishing materials	ABS
Product weight (g)	300
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes

**AUDIO FEATURES**

Microphone	9.6 (Ø) x 6.9mm, omnidirectional
Loudspeaker	50mm (Ø), 50 Ohm, 0.25W
Technologies implemented	Full-Duplex

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷35VDC
Maximum absorption (W)	0.8

**HARDWARE FEATURES**

Type of buttons	Mechanical
Service buttons	Lock-release
Clamps	L L CFP CFP



**2738W/A**

**SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET**

**HARDWARE FEATURES**

Number of inputs (n°)

1

**SETTINGS**

Ringtone volume

Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Operating temperature (°C)

-5 ÷ 40

Operating humidity (RH max) (%)

25 ÷ 90

Environmental class

III

CE certifications

RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**GENERAL FEATURES**

Door opener

Yes

Absorption during call (mA)

25

Absorption during communication (mA)

20

Maximum current absorption (mA)

25

Minimum current absorption (mA)

1

CPS call

Yes

Actuator control

Yes

Outside door call input

Yes

Silent mode (Privacy)

Yes

**2738W/A****SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET****ACCESSORIES****2711W MINI HS DOOR-ENTRY PHONE ADAPTER PLATE****2735 Ch. repeat. card+Mini HS door-entry phone button**

Additional board for door-entry phones art. 2708W/A and 2738W/A for call repetition and for an additional button with voltage free contacts. Cable for connection to the main board and fixing screws provided.

**2720W BRACKET FOR THROUGH-ROUTING OF EXTERNAL CABLES. MINI SERIES**

Surface-mounted support for Mini door-entry phones with handset, allowing external routing of cables

**2742W DESK BASE FOR MINI DOOR-ENTRY PHONE WITH HANDSET**

Desk base for desktop conversion of MINI series door-entry phones. Complete with 1.5 m cable and connection coupling.