





**2738W/A**

**SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET**

**GENERAL DATA**

Height (mm)	190
Depth (mm)	28
Type of finishing materials	ABS
Product weight (g)	300
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes

**AUDIO FEATURES**

Microphone	9.6 (Ø) x 6.9mm, omnidirectional
Loudspeaker	50mm (Ø), 50 Ohm, 0.25W
Technologies implemented	Full-Duplex

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷35VDC
Maximum absorption (W)	0.8

**HARDWARE FEATURES**

Type of buttons	Mechanical
Service buttons	Lock-release
Clamps	L L CFP CFP



**2738W/A**

**SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET**

**HARDWARE FEATURES**

Number of inputs (n°)

1

**SETTINGS**

Ringtone volume

Yes

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

Operating temperature (°C)

-5 ÷ 40

Operating humidity (RH max) (%)

25 ÷ 90

Environmental class

III

CE certifications

RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**GENERAL FEATURES**

Door opener

Yes

Absorption during call (mA)

25

Absorption during communication (mA)

20

Maximum current absorption (mA)

25

Minimum current absorption (mA)

1

CPS call

Yes

Actuator control

Yes

Outside door call input

Yes

Silent mode (Privacy)

Yes

